


# PCI-7031

Intel® Atom™ N450/D510 PCI Half-size SBC with Onboard DDR2/VGA/LVDS/Dual GbE/SATA/COM



## Features

- Ultra low power, fanless Intel® Atom™ processor N450 CPU and 1 GB onboard DDR2 667 memory (Only for N SKU)
- Dual Core™ high performance D510 CPU and maximum 2 GB DDR2 667 memory (For both D & DF SKUs)
- VGA/LVDS dual video outputs
- Optional module for 4 x RS-485 w/auto-flow control
- Supports embedded software APIs and Utilities

### Software APIs:



### Utilities:




Note: eSOS needs ODM BIOS available by request

## Specifications

Processor System	CPU	Intel Atom N450	Intel Atom D510
	Speed	1.66 GHz	1.66 GHz
	L2 Cache	512 KB	1 MB
	Chipset	ICH8M	
	BIOS	AMI 16Mb SPI Flash	
Bus	PCI-Express	-	
	PCI	Four 32 bit/33 MHz PCI Masters to Backplane	
Memory	Technology	Single channel DDR2 667 MHz	
	Max. Cap.	1 GB onboard for N SKU; max 2 GB SODIMM for D SKU	
	Socket	No socket for N SKU; 200-pin SODIMM x 1 for D SKU	
Graphics	Onboard	Embedded Gen3.5+ GFX Core technology, DirectX 9/Pixel Shader 2.0 compliant	
	VRAM	Shared 224 MB	
	Video Interface	15-pin VGA D-sub connector x1/Onboard LVDS pin header x 1 (supports single channel 18-bit LVDS)	
Video Output	VGA	Supports up to SXGA 1400 x 1050 @ 60 Hz for N SKU, up to 2048 x 1536 @ 60 Hz for D & DF SKU	
	LVDS	Supports 18-bit single channel and up to WXGA 1366 x 768 or 1280 x 800 for N, D, & DF SKUs	
Ethernet	Interface	10/100/1000 Mbps	
	Controller	LAN1: Intel 82567V LAN2: Intel 82583V	
SATA	Connector	RJ-45 with LED Connector x 2	
	Max. Transfer Rate	300 MB/s	
EIDE	Channel	3	
	Mode	ATA 100/66/33	
I/O Interface	Channel	1 (supports up to 2 IDE devices)	
	USB 2.0	7 ports on the SHB	
	Serial	Two RS-232 onboard pin-headers, plus four RS-485 ports with auto-flow control by module (Optional, Advantech P/N: PCA-COM485-00A1E)	
	Parallel	1 (EPP/ECP)	
	FDD	1	
Watchdog Timer	PS/2	1 (for mouse and keyboard, an Y cable is included in the package)	
	Output	System reset	
Miscellaneous	Interval	Programmable, 1~255 sec	
	Audio Output	Intel High Definition audio interface (requires a audio extension module, P/N: PCA-AUDIO-HDA1E)	
Environment	Operating	Operating	Non-Operating
	Temperature	0 ~ 60° C (32 ~ 140° F) (operating humidity: 40° C @ 85% RH Non-Condensing)	-40 ~ 85° C and 60° C @ 95% RH Non-Condensing
Physical	Dimensions	185 mm (L) x 122 mm (W) (7.3" x 4.8")	

### Block Diagram



### Ordering Information

Model Name	CPU	Memory	Fanless	VGA	LVDS	SATA	USB	COM	CF
PCI-7031D-S6A1E	Atom™ D510	One SODIMM Socket 2 GB DDR2 667 No Onboard RAM	No	1	1	3	7	2	1
PCI-7031DF-S6A1E	Atom D510	One SODIMM Socket 2GB DDR2 667 No Onboard RAM	Yes*	1	1	3	7	2	1
PCI-7031N-S6A1E	Atom™ N450	No SODIMM Socket Onboard 1 GB DDR2 667	Yes	1	1	3	7	2	1

\*PCI-7031DF-S6A1E is only compatible with chassis: IPC-120 and backplane: PCI-7103P1V-01.

### Optional Accessories

Part Number	Description
PCA-COM485-00A1E	Extension module for four RS-422/485 ports with auto-flow control function
PCA-AUDIO-HDA1E	Extension module for 7.1 channel High Definition audio

### Bracket View



PCI-7031D-S6A1E  
 PCI-7031N-S6A1E  
 PCI-7031DF-S6A1E

### Packing List

Part Number	Description	Quantity
960046526N001	CPU cooler for Atom™ D510 CPU (only available for D SKU)	x 1
1700003194	Serial ATA HDD data cable	x 1
1703150102	Serial ATA HDD power cable	x 1
1701260301	Printer (parallel) port cable kit	x 1
1700008762	Dual COM ports cable kit	x 1
1700002343	ATX feature cable	x 1
1700014398	4-port USB cable kit	x 1
1700060202	Y cable for PS/2 keyboard and PS/2 mouse	x 1
1700000265	AT/ATX PSU 20-Pin to 12-Pin Cable Kit	x 1
9689000068	Jumper pack	x 1
-	Warranty card	x 1
-	PCI-7031 startup manual	x 1
-	CD with driver utility and manual (in PDF format)	x 1