

APAX-5040

APAX-5045

24-ch Digital Input Module

24-ch Digital Input/Output Module



APAX-5040



Specifications

General

- **Certifications** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 160 g
- **Power Consumption** 2 W @ 24 V_{DC} (typical)
- **Status Display** LED per channel
On: Logic level 1
Off: Logic level 0

Digital Input

- **Channels** 24
- **Points per Common** 12
- **Type** Sink or Source Load
- **Input Voltage** Rated Value: 24 V_{DC}
For "0" signal: -5 ~ 5 V_{DC}
For "1" signal: 15 ~ 30 V_{DC} and -15 ~ -30 V_{DC}
- **Input Impedance** 10 kΩ
- **Input Delay** From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms
- **Operating Frequency** 3 kHz
- **Input Filter** 3 ms

Protection

- **2,500 V_{DC} Isolation Between Channels and Backplane**
- **Over Voltage Protection**

Environment

- **Operating Temperature** -10 ~ 60° C (when mounted vertically)
- **Storage Temperature** -40 ~ 70° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **APAX-5040** 24-ch Digital Input Module
- **APAX-5001** 1-slot Backplane Module
- **APAX-5002** 2-slot Backplane Module
- **APAX-5343E** Power Supply for APAX Expansion Module



APAX-5045



Specifications

General

- **Certifications** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 165 g
- **Power Consumption** 2.5 W @ 24 V_{DC} (typical)
- **Status Display** LED per channel
On: Logic level 1
Off: Logic level 0

Digital Input

- **Channels** 12
- **Points per Common** 12
- **Type** Sink or Source Load
- **Input Voltage** Rated Value: 24 V_{DC}
For "0" signal: -5 ~ 5 V_{DC}
For "1" signal: 15 ~ 30 V_{DC} and -15 ~ -30 V_{DC}
- **Input Impedance** 10 kΩ
- **Input Delay** From Logic level 0 to 1: 0.2 ms
From Logic level 1 to 0: 0.2 ms
- **Operating Frequency** 3 kHz
- **Input Filter** 3 ms

Digital Output

- **Channels** 12 (Sink)
- **Voltage Range** 8 ~ 35 V_{DC}
- **Rated Current Output** 0.5 A (per channel, at signal "1")
- **Permitted Current Output** Max. 0.75 A (at signal "1")
- **Leakage Current** 0.1 mA (at signal "0")
- **Switch Rate:** Resistive load: 300 Hz (max.)
Inductive load: max. 20 Hz (max.)
Lamp load: max. 200 Hz (5W lamp and under 50 Ω, 24 V)

Protection

- **2,500 V_{DC} Isolation Between Channels and Backplane**
- **Over Voltage Protection (for DI channel)**
- **Short Circuit Protection (For DO channel)**
- **Thermal Shutdown Protection (For DO channel)**

Environment

- **Operating Temperature** -10 ~ 60° C (mounted vertically)
- **Storage Temperature** -40 ~ 70° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **APAX-5045** 24-ch Digital Input/Output Module
- **APAX-5001** 1-slot Backplane Module
- **APAX-5002** 2-slot Backplane Module
- **APAX-5343E** Power Supply for APAX Expansion Module

19 Embedded Controllers

20 PC-based Controllers

21 PAC

22 Motion Control

23 RS-485 I/O

24 Ethernet I/O

25 Building Automation

26 Self-service Terminals

27 eHome Platforms