

Extension Kit



Advantech offers an optional second-stack extension kit for expanding the system functionalities

UNO-137-ID1EA

Second-stack extension kit with 1 x iDoor slot (for UNO-137-E13BA)




Specifications

General	
Ports	1x iDoor slot
Dimensions (W x D x H)	35 x 105 x 150 mm (1.4 x 4.1 x 5.9 in)
Weight	0.2 kg (0.4 lb)

Note: The system operating temperature can be maintained at 60 °C/140 °F with most iDoor modules (excluding PoE and USB 3.0 modules)

Front I/O



Ordering Information

Part Number	Description
UNO-137-ID1EA	UNO-137 second-stack extension kit with 1 x iDoor slot

Supported iDoor Modules

iDoor Industrial Fieldbus Communication	
PCM-26D2CA-AE	2-port isolated CANBus mPCle, CANopen, DB9
PCM-26D1DB-MAE/SAE	1-port Hilscher netX100 FieldBus mPCle, PROFIBUS, DB9, Master/Slave
PCM-26R2PN-MAE/SAE	2-Port Hilscher netX100 FieldBus mPCle, PROFINET, RJ45, IO-Controller / IO-Device
PCM-26R2EC-MAE/SAE	2-port Hilscher netX100 FieldBus mPCle, EtherCAT, RJ45, MainDevice (abbreviated MDevice) / SubordinateDevice (abbreviated SubDevice)
PCM-26R2EI-MAE/SAE	2-port Hilscher netX100 FieldBus mPCle, EtherNet/IP, RJ45, Scanner / Adapter
PCM-26R2PL-MAE/SAE	2-port Hilscher netX100 FieldBus mPCle, POWERLINK, RJ45
iDoor Smart Digital/Analog I/O	
PCM-24D2R4-BE	2-port isolated RS-422/485, mPCle, DB9
PCM-24D2R2-BE	2-port isolated RS-232, mPCle, DB9
PCM-24D4R4-BE	4-port non-isolated RS-422/485 mPCle, DB37 cable
PCM-24D4R2-BE	4-port non-isolated RS-232 mPCle, DB37 cable
PCM-24R1TP-AE	1-port Gigabit Ethernet, Intel® 82574L, mPCle, RJ45
PCM-24R2PE-AE	2-port Gigabit Ethernet, IEEE 802.3af (PoE)- compliant, mPCle, RJ45
PCM-24R2GL-AE	2-port Gigabit Ethernet, Intel® i350, mPCle, RJ45
PCM-27D24DI-AE	24-channel isolated digital I/O with counter mPCle, DB37
iDoor CORE	
PCM-2300MR-AE	MR4A16B, MRAM, 2 MB, mPCle
PCM-23C1CF-BE	1 x CFast slot with cover protection
PCM-23U1DG-CE	USB slot w/ lock for USB dongle, half-size mPCle
PCM-24U2U3-BE	2-port USB 3.0, mPCle, USB-A type
PCM-27J3AU-AE	3-port audio stereo, mPCle, 3.5-mm jack
iDoor Wired/Wireless Communication	
PCM-24S2WF-BE	Wi-Fi 802.11 a/b/g/n 2T2R w/Bluetooth 4.0, half-size mPCle, antennas
PCM-24S34G-EBE	LTE/HSPA+/GPRS and GPS, full-size mPCle, 4G/GPS antennas for EMEA/APAC
C-PCM-24S24G-4AV-1	Cellular iDoor module, LTE Cat. 4 for AT&T/Verizon
C-PCM-24S24G-1A-1	Cellular iDoor module, LTE Cat. 1 for AT&T
C-PCM-24S24G-1V-1	Cellular iDoor module, LTE Cat. 1 for Verizon
C-PCM-24S24G-MAV-1	Cellular iDoor module, LTE Cat. M1 for AT&T/Verizon